

Narrow Back Bar Series

24" depth • 3 sizes • 3 styles



FEATURES

Double paned glass with tempered outer glass or foamed in place polyurethane insulated solid doors
Left side mounted front venting compressor using R290 hydrocarbon refrigerant
304 stainless steel or wear resistant black vinyl coated steel exterior; 304 stainless steel top and interior
LED interior lighting with separate power switch
4 or 6 individually adjustable epoxy coated 90 lb. capacity shelves
Dixell digital controller with automatic defrost programming
Self-evaporating water tray – no drain needed
ETL Listed and conforms to NSF Std. 7
Standard 15 amp plug



WARRANTY



Parts & Labor

+



Compressor
part only

| Model | Doors | Exterior | HP | Amps | Volume | Width | Depth | Height |
|-------------|----------|-----------|-----|------|--------------|----------------------------|--------------------------|--------------------------|
| IM48NBB2-B | 2, Solid | Black | 1/5 | 2.88 | 11.8 Cu. Ft | Ext: 48.8" Int: 36.25" | Ext: 24.4" Int: 18.5" | Ext: 35.6" Int: 28.9" |
| IM48NBBG2-B | 2, Glass | Black | | | | | | |
| IM48NBBG2-S | 2, Glass | Stainless | | | | | | |
| IM60NBB2-B | 2, Solid | Black | 1/5 | 2.88 | 15.8 Cu. Ft | Ext: 60.75" Int: 48.25" | Ext: 24.4" Int: 18.5" | Ext: 35.6" Int: 28.9" |
| IM60NBBG2-B | 2, Glass | Black | | | | | | |
| IM60NBBG2-S | 2, Glass | Stainless | | | | | | |
| IM72NBB2-B | 3, Solid | Black | 1/4 | 3.96 | 19.6 Cu. Ft. | Ext: 72.75" Int: 60.1" | Ext: 24.4" Int: 18.5" | Ext: 35.6" Int: 28.9" |
| IM72NBBG2-B | 3, Glass | Black | | | | | | |
| IM72NBBG2-S | 3, Glass | Stainless | | | | | | |

